



Agile, compact, powerful.



Technical data

GXV 160 without hydraulic		GXV 340 without hydraulic	
GXV 160 Honda	Engine (petrol)	GXV 340 Honda	
82 dB	Volume	82 dB	
3,2 KW	Power	6,6 KW	
hydrostatic	Drive	hydrostatic	
6 km/h	Speed	6 km/h	
hand start	Start	electric start	
no	Hydraulic	no	
without	Hydraulic power	without	
rear wheel steering	Steering	rear wheel steering	
approx. 200 kg (additional weights possible as required)	Weight	approx. 225 kg (additional weights possible as required)	
L = 1800 mm, B = 770 mm, H = 1070 mm	Size	L = 1800 mm, B = 770 mm, H = 1070 mm	
5 mm galvanized	Chassis	5 mm galvanized	
AS tires 16 x 6.50-8	Tires	AS tires 16 x 6.50-8	
mechanically possible	Lifting of attaching machines	mechanically possible	
including operating hours counter	Lighting	including operating hours counter	
scraper, pushing shield, snow plough	Accessories	scraper, pushing shield, snow plough	
	Mounting options		
GXV 340 with hydraulic		Vanguard 2 cylinder with hydraulic	
GXV 340 Honda	Engine (petrol)	Briggs & Stratton Vanguard	
82 dB	Volume	82 dB	
6,6 kw	Power	11,9 kw	
hydrostatic	Drive	hydrostatic	
6 km/h	Speed	6 km/h	
electric start	Start	electric start	
with	Hydraulic	with	
13 ltr. / min (18 ltr. / min in consultation)	Hydraulic power	13 ltr. / min (18 ltr. / min in consultation)	
rear wheel steering	Steering	rear wheel steering	
approx. 270 kg (additional weights possible as required)	Weight	approx. 270 kg (additional weights possible as required)	
L = 1800 mm, B = 770 mm, H = 1070 mm	Size	L = 1800 mm, B = 770 mm, H = 1070 mm	
5 mm galvanized	Chassis	5 mm galvanized	
AS tires 16 x 6.50-8	Tires	AS tires 16 x 6.50-8	
mechanically or hydraulically possible	Lifting of attaching machines	mechanically or hydraulically possible	
including operating hours counter	Lithing	including operating hours counter	
radial brush, weed brush, axial sweeper, snow plough, pushing shield, feed auger, scraper, washer, spreader, lime and feed spreader, trough washer	Accessories	radial brush, weed brush, axial sweeper, snow plough, pushing shield, feed auger, scraper, washer, spreader, lime and feed spreader, trough washer	
	Mounting options		

(Technical data is approximate and non-binding.)

ATTACHING MACHINES FOR CLEANMELEON 2

Radial brush R 900



- working width: 900 mm
- sturdy and stable bristles for moving large quantities of debris
- direction of rotation of the brush: right-left rotation
- easy change of bristle set

Radial brush R 1000



- working width: 1000 mm
- for sweeping large quantities of debris
- direction of rotation clockwise / counterclockwise adjustable
- bristle set quickly changeable over screws

Radial brush R 1000 (wire)



- working width: 1000 mm
- wire brush
- excellent and sustainable green removal on a fixed surface at regular use

Weed brush WKB 550 (wire)



- working width: 550 mm
- stable wire braids remove moss and strong greens effectively
- manual arm 180 ° from left to right swiveling

Axial sweeper AX 900



- overhead sweeping principle with oscillating suspended sweeping roller
- leading roll-off lip pushes the dirt to the brush
- expandable with up to two side brushes

Feed auger FA 800



- working width: 800 mm
- open windings loosen and evaluate this feed and return to the animal
- additional side brush available

more mounting options →

ATTACHING MACHINES FOR CLEANMELEON 2

Scraper ASS 800 / ASS 900



- working width: 800 or 900 mm
- C-shaped front doesn't let mess drift away
- also additional side brush available for cleaning the lying areas

Washer SW 800



- working width: 800 mm
- including 150 l water canister, filter, high pressure pump, clearing stars,
- accessories: adapters for high-pressure nozzle

Spreader EG 580



- high-quality, robust guide wheels
- flexible spreading paddles convey the spreading material out
- self-filling by tipping down the container over hydraulic cylinder
- also available as a trailer version

Lime and feed spreader



- ideal for evenly spreading lime
- can also be used as a concentrate feeder
- with dosing opening in the manually swiveling ejector

Pushing shield 80 - 160



- perfect for narrow passages
- working width is flexible adjustable from 80 to 160 cm via perforated strip

Snow plough 1600



- working width: 1600 mm with robust protective edge
- swiveling left and right
- suitable for dirt and snow sliding