

The diesel machine.



The diesel-powered machine has an extremely stable adapter triangle. This makes it possible to use heavy and particularly powerful attachments.

Technical data

	Cleanmeleon 2 XL
Engine (diesel)	Kubota Z602, 2-cylinder water cooled
Volume	82 dB
Power	10.3 kw
Drive	all-wheel, axial piston pump
Speed	infinitely up to 10 km / h
Start	incl. preheating automatic
Hydraulic	with
Hydraulic power	24 l / min.
Steering	rear wheel steering
Weight	approx. 405 kg (additional weights possible as required)
Size	L = 1805 mm, B = 832 mm, H = 1275.3 mm
Chassis	8 mm galvanized
Tires	AS tires 18 x 8.50-8
Lifting of attaching machines	hydraulically
Lighting	LED lighting front
Accessories	incl. operating hours counter
Attachment options	radial brush, spreader, scraper, washer, pushing shield, snow plough, snow blower

(Technical data is approximate and non-binding.)



ATTACHING MACHINES FOR CLEANMELEON 2 XL



- working width: 1000 mm
- for sweeping large quantities of debris
- direction of rotation clockwise /counterclockwise adjustable
- bristle set quickly changeable over screws





- working width: 800 mm
- open windings loosen and evaluate this feed and return to the animal
- additional side brush available





- working width: 800 or 900 mm
- C-shaped front doesn't let mess drift away
- also additional side brush available for cleaning the lying areas



- working width: 1000 mm
- wire brush
- excellent and sustainable green removal on a fixed surface at regular use





- high-quality, robust guide wheels
- flexible spreading paddles convey the spreading material out
- Self-filling by tipping down the front shovel





- working width: 900 mm
- including 150 l water canister, filter, high pressure pump, clearing stars,
- accessories: adapters for high-pressure nozzle



ATTACHING MACHINES FOR CLEANMELEON 2 XL



- perfect for narrow passages
- working width is flexible adjustable from 80 to 160 cm via perforated strip



- working width: 1000 mm
- ejector rail is manually swiveling to the left and right



- working width: 1600 mm with robust protective edge
- swiveling left and right
- suitable for dirt and snow sliding

